

ORAJET® Series 3169RA Intermediate Removable Calendered Digital Media with RapidAir® Technology

Description

A 4-mil special PVC film available in white with a gloss or matte surface.

Release Liner

101# PE-coated silicone paper

Adhesive

Solvent polyacrylate, removable, grey

Applications

For flat indoor and outdoor short- to medium-term applications. Ideal for general signage, POP, and partial vehicle wraps requiring limited conformability.

Technical Data

Thickness (without protective paper and adhesive)	4 mil
Dimensional stability (FINAT TM 14)	Adhered to steel, no shrinkage in cross direction, in length 0.016" max.
Temperature resistance	Adhered to aluminium, -40°F to 176°F, no variation
Sea water resistance (DIN 50021)	Adhered to aluminium, after 100h/73°F no variation
Fire behavior	Adhered to steel, self-extinguishing
Fire rating	ASTM E 84-07 Class "A"
Adhesive power (FINAT TM 1, after 24h average)	Adhered to stainless steel: 1.8 lb/in
Tensile strength (DIN EN ISO 527)	along: min. 19 MPa across: min. 19 MPa
Elongation at break (DIN EN ISO 527)	along: min. 130% across: min. 150%
Shelf life	2 years
Minimum application temperature	46°F
Minimum life expectancy (based on accepted application procedures on vertical surfaces)	5 years (not printed)
Available Widths	54"
Available Lengths	50 yd (150 ft)
Recommended Laminates	ORAGUARD® Series 210, 215, 240

Attention

Recycling Recommendation: Waste class similar to household waste, is to be recycled according to the local regulations.

Surfaces to which the material will be applied must be cleaned thoroughly of dust, grease or any contaminants. Freshly lacquered or painted surfaces should be allowed to stand for at least three weeks after complete curing. The compatibility of selected lacquers and paints should be tested by the end-user prior to use.

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without any guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications, customers should independently determine the suitability of this material for their specific purpose, prior to use.

For instant access to more information click on the links below

Visit Oracal.com

<http://www.oracal.com/>

Tech Support

<http://www.oracal.com/knowledge/contact-support.asp>

Find a Distributor

<http://www.oracal.com/distributors/>

General Warranty

http://www.oracal.com/_userfiles/File/GeneralWarranty.pdf



Revised 06/11